



MKT3H

■ Unutrašnja jedinica jednostavne ugradnje:

- Veliki protok vazduha
- Filteri spadaju u standardnu opremu

Tip MKT3H	800G70	1000G70	1200G70	1400G70	1600G100	1800G100	2200G100
-----------	--------	---------	---------	---------	----------	----------	----------

Maksimalni protok vazduha	m ³ /h	1360	1700	2040	2380	2720	3060	3740	
Kapacitet hlađenja	BTU/h	6.850	9.250	12.300	15.350	18.450	24.550	30.700	
	kW	6.5	8.8	10	12	14.10	15.8	19.9	
Kapacitet grejanja	kW	9.7	13.20	15	17.90	21.20	23.80	30	
Pomoćni električni grejač	kW	5	5	5	5	10	10	10	
Protok vode	m ³ /h	1.11	1.51	1.71	2.05	2.42	2.72	3.43	
Pad pritiska vode	kPa	8	24	24	36	52	90	130	
Usisna / potisna cev		3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	
Nivo buke	dB	62	61	61	60	62	63	66	
Težina	kg	50	52	52	54	76	76	76	
Eksterni statički pritisak	Pa	70				100			

Dimenzije	mm	946x400x816				1290x400x809		
-----------	----	-------------	--	--	--	--------------	--	--



- Trokraki ventil naručuje se opcionalno
- KJR-18B/E ili CE-KJR-21B/D termostat (opcionalno)
- Tipična primena hotelska soba
- Nizak nivo buke



KJR-18B/E



CE-KJR-21B/D